

Silent Space®

Le silence a un son.

Technical specifications



Controller



Diffuser



Led Diffuser

Power supply	110 à 240 V (50/60 Hz)		
Energy Consumption	< 2 W		
Electrical connection	Large screw base E27		
Diameter	97 mm		
High	89 mm	98 mm	106 mm
Weight	≤ 140 g	≤ 200 g	≤ 240 g
Wireless connection	Bluetooth LE		
Range	10 m		
Number of diffusers	≤ 6	-	-

Setting

Smartphone App	Android ≥ 4.3
ON / OFF	Setting of the working week days Setting the START time and the STOP time of each working day Setting of the switch-on and switch-off speed with a 0.1 dB precision
Adjustment of the masking signal	Setting up to 8 thresholds, minimum steps of 1 dB(A) Setting the adjustment speed of the masking signal level 0.1 dB/s Setting of the initial base level of each diffusor
Implantation scenario	Possibility to define a delayed start of the system Progressive increase of the masking signal over several days
Measurement settings (controller)	Measurement dynamic of 40 dB(A), from 30 to 70 dB(A) Adjustable integration time from 1 to 60 seconds Backup of the morning, afternoon and day average noise level Backup of the data during 365 days
LED Options	Setting of the light color Setting up to 8 noise level threshold Light color transition speed

Orfea Acoustique Développement

33 rue de l'île du roi - BP 40098 - 19103 BRIVE CEDEX - France
+33 (0)5 55 86 34 50 / www.silent-space.fr / contact@silent-space.fr